



ООО «Компрессоры Без Масла»

+7 (812) 244-93-00

www.kbm-spb.com

info@kbm-spb.com

**Характеристики спиральных компрессоров "OF Kompressoren"**

Модель	Производительность, л/мин		Осушитель	Ресивер, л	Прсоед.	Уровень шума, дБ(А)	Габариты, мм
	8 бар	10 бар					
OF 1,5	160	-	-	-	G 1/2	52 / -	910x550x920
OF 2,2	238	195	-	-	G 1/2	55 / 53	910x550x920
OF 3,7	397	-	-	-	G 1/2	54 / -	910x550x920
OF 4,5	-	405	-	-	G 1/2	- / 54	910x550x920
OF 5,5	627	520	-	-	G 1/2	59 / 57	910x550x920
OF 7,5	794	-	-	-	G 1	58 / -	1400x920x1020
OF 9,0	-	810	-	-	G 1	- / 59	1400x920x1020
OF 11,0	1254	1040	-	-	G 1	61 / 60	1400x920x1020
OF 13,5	-	1215	-	-	G 1	- / 62	1400x920x1890
OF 15	1780	-	-	-	G 1	65 / -	1400x920x1020
OF 16,5	1880	1560	-	-	G 1	64 / 63	1400x920x1890
OF 22	2510	2080	-	-	G 1	66 / 65	1400x920x1890
OF 22,5	2670	-	-	-	G 1	68 / -	1400x920x1890
OF 30	3560	-	-	-	G 1	71 / -	1400x920x1890
OFR 1,5	160	-	-	90*	G 1/2	52 / -	1224x550x1390
OFR 2,2	238	195	-	90*	G 1/2	55 / 53	1224x550x1390
OFR 3,7	397	-	-	250**	G 1/2	54 / -	1410x570x1550
OFR 4,5	-	405	-	250**	G 1/2	- / 54	1410x570x1550
OFR 5,5	627	520	-	250**	G 1/2	59 / 57	1410x570x1550
OFR 7,5	794	-	-	500	G 1	58 / -	1670x920x1811
OFR 9,0	-	810	-	500	G 1	- / 59	1670x920x1811
OFR 11,0	1254	1040	-	500	G 1	61 / 60	1670x920x1811
OFT 1,5	160	-	+3 оС	-	G 1/2	52 / -	1165x550x920
OFT 2,2	238	195	+3 оС	-	G 1/2	55 / 53	1165x550x920
OFT 3,7	397	-	+3 оС	-	G 1/2	54 / -	1165x550x920
OFT 4,5	-	405	+3 оС	-	G 1/2	- / 54	1165x550x920
OFT 5,5	627	520	+3 оС	-	G 1/2	59 / 57	1165x550x920
OFT 7,5	794	-	+3 оС	-	G 1	58 / -	1400x920x1020
OFT 9,0	-	810	+3 оС	-	G 1	- / 59	1400x920x1020
OFT 11,0	1254	1040	+3 оС	-	G 1	61 / 60	1400x920x1020
OFT 13,5	-	1215	+3 оС	-	G 1	- / 62	1400x920x1890
OFT 16,5	1880	1560	+3 оС	-	G 1	64 / 63	1400x920x1890
OFT 22	2510	2080	+3 оС	-	G 1	66 / 65	1400x920x1890
OFTR 1,5	160	-	+3 оС	90*	G 1/2	52 / -	1224x550x1390
OFTR 2,2	238	195	+3 оС	90*	G 1/2	55 / 53	1224x550x1390
OFTR 3,7	397	-	+3 оС	250**	G 1/2	54 / -	1410x570x1550
OFTR 4,5	-	405	+3 оС	250**	G 1/2	- / 54	1410x570x1550
OFTR 5,5	627	520	+3 оС	250**	G 1/2	59 / 57	1410x570x1550
OFTR 7,5	794	-	+3 оС	500	G 1	58 / -	1670x920x1811
OFTR 9,0	-	810	+3 оС	500	G 1	- / 59	1670x920x1811
OFTR 11,0	1254	1040	+3 оС	500	G 1	61 / 60	1670x920x1811

Данные на компрессоры серий OFA и OFRA (с адсорбционным осушителем) по запросу.

**Характеристики  
винтовых безмасляных компрессоров  
"OF Kompressoren" (Германия)**

Модель	Производительность м3/мин				Мощность кВт	Звуковое давление <sup>1</sup> дБ(А)	Соед.	Габариты мм	Вес кг
	6 бар	8 бар	10 бар	13 бар					
WSF 26,0	1,75-4,30	2,00-4,20	2,20-3,90	-	26	69	1 1/2	2147x942x1333	680
WSF 26,0*	1,75-4,30	2,00-4,20	2,20-3,90	-	26	69	1 1/2	2161x942x1850	740
WSF 37,0	1,55-7,10	1,55-6,49	1,55-5,54	1,55-4,77	37	74	DN 50	2060x1260x1732	1580
WSF 40,0	1,75-6,30	2,00-6,00	2,20-5,40	2,70-4,80	40	74	DN 40	2147x942x1333	950
WSF 40,0*	1,75-6,30	2,00-6,00	2,20-5,40	2,70-4,80	40	74	DN 40	2161x942x1850	1070
WSF 45,0	1,55-8,00	1,55-7,74	1,55-6,58	1,55-5,65	45	74	DN 50	2060x1260x1732	1650
WSF 50,0	1,55-10,30	1,55-9,60	1,55-8,00	-	50	74	DN 50	2060x1260x1732	1650
WSF 68,0	1,55-11,25	1,55-11,20	1,55-10,25	-	68	74	DN 50	2060x1260x1732	1650
WSF 85,0	1,55-12,36	1,55-12,17	1,55-10,17	-	85	76	DN 50	2060x1260x1732	1750
WSF 90,0	3,41-16,60	3,41-15,80	3,41-14,30	-	90	74	DN 65	2525x1571x1832	2280
WSF 120,0	3,41-20,60	3,41-20,30	3,41-17,65	3,41-15,40	120	74	DN 65	2525x1571x1832	2390
WS 18,5*	3,10	3,05	3,00	-	18,5	69	DN 40	2161x942x1850	740
WS 18,5	3,10	3,05	3,00	-	18,5	69	DN 40	2147x942x1333	620
WS 22,0*	3,10	3,05	3,00	2,95	22	69	DN 40	2161x942x1850	750
WS 22,0	3,10	3,05	3,00	2,95	22	69	DN 40	2147x942x1333	630
WS 37,0	5,80	5,65	5,60	-	37	69	DN 50	2060x1260x1732	1520
WS 45,0	5,80	5,65	5,60	5,40	45	69	DN 50	2060x1260x1732	1550
WS 75,0	12,00	11,85	11,75	11,50	75	74	DN 65	2200x1500x1832	1050

\* Воздушное охлаждение

1) nach CAGI PNEUROP PN 8 NTC



**Серия WS**



**Серия WSF**



**Серия OF и OFT**



**Серия OFR и OFTR**